


# PRODUCTION CONTROL WHERE IT COUNTS

## 2" Diameter Tower Light

## Auto Escalation Call Light

120VAC power  
9VDC Contact Closure Input



**Auto Escalation Call Light-** Call light offers customer the ability to easily identify and prioritize machines needing attention the most. Locate areas that have been down the longest based on color and flash pattern activated.

Example 5 minute escalation 3 step:

Operational = Solid Green Light  
0-5 Minutes Down = Solid Yellow Light  
5-10 Minutes Down = Solid Red Light  
10+ Minutes Down = Flashing Red Light

Model #	Description
ST-4003-905	LED, R/Y/G, 120VAC, 9VDC alarm input

- Red, Yellow, Green
- Easy Install
- 2" Diameter Light
- LED
- ABS Box w/AC Power Cord
- 9VDC Contact Closure "Alarm" Input

Operation: Upon power unit will activate solid on green. Upon contact closure of "alarm" input, unit will auto internally time up each interval and activate solid or flashing light state for each step as programmed via dip switches.

Switch selection for interval time and steps. Auto escalation interval time can be set between 1 minute up to 127 minutes. All steps must be equal interval times (i.e. all steps are 5 minutes each).

Steps available in 3 or 4.

3 Step = auto activation of solid yellow first, followed by solid red, then flashing red state.

4 Step=auto activation of solid yellow first, then flashing yellow, followed by solid red, then flashing red state.

Pre-assembled with light stack, 2" pole, ABS box, 120VAC, industry standard, 5 foot, 3 prong power cord and a cable gland/ hole for customer to wire in. Power is 120VAC.

Standard Stack Light specs and features: LED lighting. Lens made of heat & shock resistant polycarbonate resin. Prism cutting lens design provides superior light diffusion. Colors available in red, yellow, green.

Lights are IP65. Standard light size is 52mm (2 inch) diameter. Bulbs 120VAC 5W LED.

