

# PRODUCTION

## CONTROL WHERE IT COUNTS

1.0" L.E.D. Timer  
HHHHH.tenths

### 1.0" LED 6 Digit Maintenance Timer

120VAC POWER  
MACHINE/SWITCH  
OUTPUT ACTIVATED

The Trimline Maintenance Timer is an effective tool to assist maintenance with realtime data display. Maintenance can monitor/easily identify how long a machine has been operating with a glance.

One inch six digit red numeric timer display with custom module rotation for decimal use in tens position. Interface is 24 Vdc or 120 VAC passive. Standard Logic Inputs are provided for Run (time up) and Reset. Maintained run input. Momentary reset. Power is 120 Vac at 1 amp. Cabinet is NEMA 1. Dimensions including eyelets and wall mount tabs: 12.25" wide by 6.75" tall by 2.75" deep. Memory backup. HHHHH.T (tenths of hour) format.

TL-2410-900 model offers led timer only with pig tail wire out of the side for customer termination.

TL-2410-901 model offers led timer with pre-wired 15 foot cable to an ABS box with run/hold switch and reset button. 22mm switch size.

Models come pre-wired with 120VAC power cord.

#### MODEL # TL-2410-900

1.0" LED MODEL WITH PIG TAIL WIRE  
(NO SWITCH BOX)

List Price \$ 595.00 + freight

#### MODEL # TL-2410-901

1.0" LED MODEL WITH SWITCH BOX

List Price \$ 726.00 + freight



- 120VAC Power
- 1.0" LED Height (50' view)
- Red LED Numeric
- NEMA1 Black Extruded Aluminum
- Wall Mount Tabs

#### SPECS

**AC Supply Voltage:**-----120 VAC at ½ AMP, 60 Hz  
**Logic Input Voltage:**-----120 VAC  
**Operating Temperature:** --- 0 F to 135 F (-17C to +50C)  
**Housing/Enclosure:**----- NEMA 1, Black extruded aluminum  
**Housing Dimensions:**----- 12.25" wide by 6.75" tall by 2.75" deep.  
**Character Height:**----- 1.0" High 7-segment L.E.D. Modules  
Available in Red  
**L.E.D. Life:**-----100,000 Hours (11.4years)  
**Viewing Range:**----- Up to 50 Feet, single sided unit  
**Optional Switch Box:**----- ABS with 15' cable  
**Optional Box Dim.:**----- 2.625" W x 4.1" T x 2.625" D  
**Optional Switches:**----- 22mm on/off and push button

#### Interested in customizing your own timer?

American LED-gible can customize any hardware design or operation firmware to fit your desired operation. Contact us to discuss your particular timer requirements and sales will update with pricing on a unit to fit.



Sample unit is custom time up timer with red/yellow/green indicator panel for activation at user PC programmed trip points.

**American LED-gible**  
Quality displays you can count on.

**American LED-gible Inc.**  
1776 Lone Eagle Street Columbus, Ohio 43228  
Phone: 614-851-1100 Fax: 614-851-1121

