



22MM L.E.D. INDICATORS

These indicator lamps are unlike standard indicators that use LED technology with transparent lens. We provide diffused translucent lens to give the user an even color dispersion for greater visibility.

Common Uses:

- Machine Faults
- Alarm Indication
- Alert Systems
- Access Indication
- Assistance Indication
- Process Status

FEATURES/OPERATION

- ✓ L.E.D.
- ✓ DIFFUSED TRANSLUCENT LENS FOR EVEN COLOR
- ✓ 24VDC OR 120 VAC

SPECIFICATIONS

| |
|--|
| LED: 22mm round in either red, yellow, green blue or white |
| Use: Indicator Lamp |
| Intensity: 75mcd or greater |
| Temperature: -25 to 60 C, 50,000 hours |
| Rating: CE, TUV marking |

| VOLTAGE | COLOR | PART # | \$ PER |
|---------|--------|-------------|--------|
| 24VDC | RED | LD-2837-122 | 9.95 |
| 24VDC | YELLOW | LD-2837-123 | 9.95 |
| 24VDC | GREEN | LD-2837-125 | 9.95 |
| 24VDC | BLUE | LD-2837-126 | 9.95 |
| 24VDC | WHITE | LD-2837-129 | 9.95 |
| 120VAC | RED | LD-2837-112 | 9.95 |
| 120VAC | YELLOW | LD-2837-113 | 9.95 |
| 120VAC | GREEN | LD-2837-115 | 9.95 |
| 120VAC | BLUE | LD-2837-116 | 9.95 |
| 120VAC | WHITE | LD-2837-119 | 9.95 |

Need something custom?
Give us a call.



Phone: 614-851-1100

American LED-gible Inc.

1776 Lone Eagle Street Columbus, Ohio 43228

Phone: 614-851-1100 Fax: 614-851-1121

www.ledgible.com

www.ledandon.com